

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
13 January 2005 (13.01.2005)

PCT

(10) International Publication Number  
**WO 2005/002765 A1**

(51) International Patent Classification<sup>7</sup>: **B22F 7/06**

(21) International Application Number:  
PCT/KR2004/001640

(22) International Filing Date: 2 July 2004 (02.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
10-2003-0045820 7 July 2003 (07.07.2003) KR

(71) Applicant and

(72) Inventor: **KIM, HYO YOUNG** [KR/KR]; 6-102 Dong-namvilla, Maetan 2-dong, Youngtong-gu, Suwon-si, Gyeonggi-do 443-801 (KR).

(74) Agent: **EUN JIN SOHN PATENT & LAW OFFICE**; 1F., Yeoksam P-Bldg., Yeoksam-Dong, Kangnam-Ku, Seoul 135-080 (KR).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: RESIN BONDING TYPE DIAMOND TOOL AND MANUFACTURING METHOD THEREOF



(57) Abstract: A resin bonding type diamond tool and manufacturing method thereof, in which the diamond tool is fabricated by preparing diamond pellets by sintering diamond powder and metal matrix, loading the diamond pellets into a mold and sintering the diamond pellets together with injected resin or powder resin. This can be applied to all tools of various shapes, in particular, complex tools having difficulty in fabrication, shorten a manufacturing process to save cost, time and molds, and remarkably improve the cutting ability of final products.

REST AVAILABLE COPY

WO 2005/002765 A1